ANDREYEVA, V.M.; SEDOVA, T.V.

Variability of the taxonomic characters of unicellular green algae in culture. Report No.1. Disappearance of the pyrenoid. Bot.zhur. 50 no.7:954-961 Jl '65.

(MIRA 18:11)

1. Botanicheskiy institut imeni Komarova AN SSSR, Leningrad.

ANDREYEVA, V. N.

5

The decomposition potentials of metallic oxide in fused phosphates. V. N. Andreeva (V. I. Lenin Polytech. Inst., Kiev). Ukrain. Khim. Zhur. 21, 509-15(1955).— The decompn. potentials of fused Na meta- and pyrophosphates were detd. by the construction of I-V curves. Two decompn. potentials were found for each of the phosphates, which proved complex-ion formation in these phosphates. The decompn. potentials of ZnO, WO_3, CdO, PbO, CaO, Fe_2O_3, NiO, CuO, MoO_3, Bi_2O_3, and Sb_2O_3 dissolved in fused $NaPO_3$ and in $Na_4P_2O_7$ were detd. The electrochem. series of metals in the fused phosphates were calcd. from the decompn.-potential values. At 1000°, the series in $NaPO_3$ was Na, Zn, W, Cd, Pb, Co, Fe, Ni, Mo, Bi, Sb, and in $Na_4P_2O_7$, Na, Zn, W, Cd, Co, Ni, Cu, Pb, Fe, Mo, Sb. The authenticity of the series was confirmed by the detn. of e.m.f. of the corresponding Jacoby-Daniell cells. The differences in the 2 series of potentials in $NaPO_3$ and in $Na_4P_2O_7$ proved the formation of different compds. in the interaction of the oxides with the 2 phosphates. The existence of several inflections on some of the I-V curves was assumed to have resulted from the decompn. of some more complex forms at high temps.   W. M. Sternberg

ANDREYEVA, V.N.

21-58-7-14/27

AUTHORS: Delimarskiy, Yu.K., Member of the AS UkrSSR, and Andrey-
eva, V.N.

TITLE: Galvanic Concentration Cells in Fused Phosphates (Gal'van-
icheskiye kontsentratsionnyye elementy v rasplavlennykh
fosfatakh)

PERIODICAL: Dopovidi Akademii nauk Ukrains'koi RSR, 1958, Nr 7,
pp 743-746 (USSR)

ABSTRACT: The authors investigated concentration cells composed of a
solution of Sb_2O_3 in the fused sodium metaphosphate. One
of the semi-elements was pure antimony oxide and the other
was the fused sodium metaphosphate in which the Sb_2O_3-con-
centration was variable. The electromotive forces of
these cells were measured, the activity and activity co-
efficients of Sb_2O_3 were calculated, and their dependence
on the concentration was established. The results are pre-
sented in a table and in graphs. In one of the graphs, Fig.
1, electromotive force E is plotted versus $lg\frac{1}{N}$ where N
means concentration, and in the other two concentrations,
N is plotted versus activity and activity coefficient re-
Card 1/2   spectively. On the basis of the E, $lg\frac{1}{N}$ - curve the authors

Galvanic Concentration Cells in Fused Phosphates
21-58-7-14/27

come to the conclusion that compounds of the antimony oxy-
polyphosphate type are formed in the investigated system,
thereby confirming an inference drawn by Bues and Gehrke
(Ref. 12) on the basis of optical studies with respect
to sodium polyphasphate. There is 1 table, 3 graphs, and
12 references, 4 of which are Soviet, 4 German, 1 French
and 3 American.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii AN UkrSSR (In-
stitute of General and Inorganic Chemistry of the AS UkrSSR)

SUBMITTED: February 4, 1958

NOTE: Russian title and Russian names of individuals and in-
stitutions appearing in this article have been used in
the transliteration.

1. Phosphates--Electrical properties   2. Antimony oxides--Electro-
chemistry   3. Electrolytic cells--Theory

Card 2/2

(SOV/21-59-6-14/27

AUTHORS: Delimarskiy, Yu. K., Academician of the AS UkrSSR, and
                Andreyeva, V. N.

TITLE: Potentiometric Determination of the Solubility of Metal
                Oxides in Fused Sodium Metaphosphate

PERIODICAL: Dopovidi Akademii Nauk Ukrains'koi RSR, 1959, Nr 6,
                pp 633 - 635   (USSR)

ABSTRACT: Having rejected the determination of the solubility of metal
                oxides in fused salts by the method of isothermic saturation
                as ill-fitted to deal with colorated fused solvents, the
                author studied this matter applying the potentiometric
                method described by H. Lux $\int$Ref. 4$\int$. At the same time, the
                author had an objective to disprove the Lux's statement, that
                CaO can be dissolved in a fused eutectic Na_2SO_4 - K_2SO_4 only
                when the electrolytic dissociation is complete. The author
                constructed a galvanic cell of Pt (O_2) / $NaPO_3$-PbC// $NaPO_3$/

Card 1/3 (O_2) Pt type, and applied the indicator platinum-oxygen

SOV/21-59-6-14/27

Potentiometric Determination of the Solubility of Metal Oxides in Fused
Sodium Metaphosphate

electrode consisting of 0.5 mm platinum wire encased in a
porcelain cover. In the galvanic cell, the author used two
crucibles of different dimensions, made of porcellain. The
larger crucible contained $NaPO_3$, the smaller (put into the
larger one) —$NaPO_3$-PbO, with different concentrations of PbO.

Electromotive force was measured by a PPTV potentiometer.
· The element was heated in an electric furnace, at an even
temperature of 720°C. Results of examinations are compiled
in tables 1 and 2. It has been found that the electromotive
force grew with the growth of oxide concentration. This
confirmed the correctness of the author's assumption, and
proved the reversibility of platinum electrode with respect
to oxygen iones. The saturated solution obtained by this
method contained 31.6% PbO, which agreed satisfactorily with
the value of 31.0% obtained by the method of isothermal
saturation. The proposed method can also be applied to
Card 2/3   other oxides.

SOV/21-59-6-14/27

Potentiometric Determination of the Solubility of Metal Oxides in Fused
Sodium Metaphosphate

There are 2 tables, 1 graph and 9 references, 4 of which
are Soviet, 2 German and 3 English

ASSOCIATION: Institut obshchey i neorganicheskoy khimii AN UkrSSR
(Institute of General and Inorganic Chemistry of the
AS UkrSSR)

SUBMITTED: Januar 14, 1959

Card 3/3

5(2)   SOV/21-59-7-15/25

AUTHOR: Delimars'kyy,Yu.K., Member of the AS UkrSSR and
               Andryeyeva, V.M. (Delimarskiy, Yu. K. and Andreyeva, V. N.)

TITLE: Chemical Galvanic Cells in Fused Phosphate Systems

PERIODICAL: Dopovidi Akademii Nauk Ukrains'koi RSR, 1959, Nr 7,
                               pp 760-765   (UkrSSR)

ABSTRACT: The authors investigated and demonstrated the repro-
               ducibility and reversibility of a platinum-oxygen
               electrode in fused sodium metaphosphate. The presence
               of such an electrode permits measuring the e.m.f. of
               chemical cells for metal oxide solutions in fused
               metaphosphate. The chemical cell e.m.f.'s were mea-
               sured with a mixed electrolyte, $PbO - NaPO_3$, in de-
               pendence on the temperature and composition. On the
               basis of these values, the partial excessive thermo-
               dynamic functions (isobaric potential, entropy, en-
               thalpy) were calculated for various concentrations
               of PbO. The thermodynamic properties of lead oxide
Card 1/2   dissolved in sodium metaphosphate indicate that there

SOV/21-59-7-15/25

Chemical Galvanic Cells in Fused Phosphate Systems

is a strong chemical interaction among the melt com-
ponents. Evidence of this is found in the magnitudes
of the partial entropy values, as well as in the con-
siderable negative deviations of the isobaric poten-
tial. There are 3 tables, 3 diagrams and 6 referen-
ces, 2 of which are Soviet and 4 American

ASSOCIATION: Instytut zahal'noyi ta neorhanichnoyi khimiyi AN URSR
(Institute of General and Inorganic Chemistry AS
UkrSSR)

SUBMITTED: February 16, 1959

Card 2/2

DELIMARSKIY, Yu.K.; ANDREYEVA, V.N.

Galvanic concentration of elements in fused phosphates. Part 1: .
Antimony oxide in sodium metaphosphate. Ukr.khim.zhur. 25 no.1:
8-13 '59.   (MIRA 12:4)

1. Kiyevskiy politekhnicheskiy institut.
          (Antimony oxides)   (Sodium phosphates)
                        (Electrochemistry)

ANDREYeVA, V. N., Cand Chem Sci -- (diss) "Electrochemical investigation of dissolved phosphates," Kiev, 1960, 13 pp. 150 cop. (Kiev State U im T. G. Shevchenko) (KL, 45-60, 122)

DELIMARSKIY, Yu.K.; ANDREYEVA, V.N.

Potentiometric determination of the solubility of metal
oxides in fused sodium metaphosphate. Zhur.neorg.khim. 5
no.5:1123-1125 My '60.   (MIRA 13:7)
            (Metallic oxides) (Sodium metaphosphate)

DELIMARSKIY, Yu.K.; ANDREYEVA, V.N.

Thermodynamic properties of lead oxide dissolved in fused sodium metaphosphate. Zhur. neorg. khim. 5 no.8:1800-1805 Ag '60.
(MIRA 13:9)

(Lead oxide)   (Sodium metaphosphate)

85600

5.4700 $2205, 1018, 1273$ S/078/60/005/009/034/040/XX
B017/B058

AUTHORS: Andreyeva, V. N., Delimarskiy, Yu. K.

TITLE: The Thermodynamic Properties of Some Metal Oxides Dissolved in Molten Sodium Metaphosphate

PERIODICAL: Zhurnal neorganicheskoy khimii, 1960, Vol. 5, No. 9,
pp. 2076 - 2083

TEXT: The oxides of bismuth, nickel, molybdenum, and antimony were dissolved in molten $NaPO_3$. Chemical electrolyte chains were formed from these solutions and their emf was determined in dependence on temperature and composition of the electrolyte. The thermodynamic functions (isobaric potential, entropy and enthalpy) as well as the activities and the coefficients of activity were calculated for Bi_2O_3 and NiO on the basis of the results obtained. The emf of the chemical chain $Bi|Bi_2O_3|O_2(Pt)$ and the emf of the chemical chain $Bi|NaPO_3 \cdot Bi_2O_3(N)|O_2(Pt)$ are given in Tables 1 and 2. Fig. 1 shows the dependence of the emf in the system

Card 1/3

85600

The Thermodynamic Properties of Some Metal   S/078/60/005/009/034/040/XX
Oxides Dissolved in Molten Sodium Metaphos-   B017/B058
phate

Bi_2O_3 - $NaPO_3$ on the molar ratio of both components. The dependence
ΔZ_{excess}.N on the molar ratio can be seen in Fig. 2. The thermodynamic
characteristics of the Bi_2O_3 - $NaPO_3$ system in dependence on the molar
ratio are summarized in Table 3. Table 4 shows the activity of Bi_2O_3 in
the Bi_2O_3 - $NaPO_3$ system at 860°C. The experimental and calculated emf
values given in Table 5 differ only slightly. The same studies were also
made for the NiO - $NaPO_3$ system, and the results are given in Tables 7 and
8 and in Figs. 3 to 5. The thermodynamic data and the activity
coefficients point towards an intensive chemical interaction of the
bismuth and nickel oxides with $NaPO_3$. The emf determination of the
chemical chains $Mo|MoO_3|O_2$(Pt) and $Mo|NaPO_3 - MoO_3(N)|O_2$(Pt) shows that
a reduction of hexavalent molybdenum sets in in this system, and com-
pounds of lower valency form. The emf values of the chain
$Mo|NaPO_3 - MoO_3(N)|O_2$(Pt) at temperatures of from 720 to 900°C are given

Card 2/3

ANDREYEV, V. N.

DELIMARSKIY, Yu.K.; ANDREYEVA, V.N.

Galvanic concentration cells in fused phosphates. Part 2: Lead
and bismuth oxides in fused sodium metaphosphate. Ukr. khim.
zhur. 27 no.2:167-170 '61.   (MIRA 14:3)

1. Institut obshchey i neorganicheskoy khimii AN USSR.
        (Electromotive force) (Lead oxide) (Bismuth oxide)

DELIMARSKIY, Yu.K., [Delimars'kyi, IU.K.] akademik; ANDREYEVA, V.N.
[Andrieieva, V.N]; KAPTSOVA, T.N.

Interaction of metal oxides with fused sodium metaphosphate.
Dop. AN URSR no.4:492-494 '62.   (MIRA 15:5)

1. Institut obshchey i neorganicheskoy khimii AN USSR.
2. AN USSR (for Delimarskiy).
          (Metallic oxides) (Sodium metaphosphates)

ANDREYEVA, V.N.

Conditioned inhibition to a system of conditioned stimuli in dogs.
Trudy Inst.fiziol. no.2:16-30 '53.   (MLRA 7:5)

1. Laboratoriya fiziologii i patologii vysshey nervnoy deyatel'nosti
(zaveduyushchiy - F.P.Mayorov).   (Conditioned response) (Inhibition)

ANDREYEVA, V.N.

Works of Russian researchers on the physiology of digestion
published prior to 1890. Fiziol. zhur. 41 no.3:433-446 My-Je
'55.   (MLRA 8:8)

1. Kabinet istorii otechestvennoy fiziologii Instituta fiziologii
im. I.P. Pavlova AN SSSR
        (GASTROINTESTINAL SYSTEM, physiology,
            disteation,hist. of research in Russia in 19th century
            review & bibliog.)

ANDREYEVA, V.N.

Effect of proloned use of caffeine on conditioned inhibition in
response to conditioned stimuli. Trudy Inst. fiziol. 6:150-161
'57.   (MIRA 11:4)

1. Laboratoriya fiziologii i patologii vysshey nervnoy deyatel'nosti
(zaveduyushchiy F.P. Mayorov).
         (CAFFEINE) (CONDITIONED RESPONSE)

ANDREYEVA, V.N.; FEDOROVA-GROT, A.K.

In memory of Daniil Il'ich Soloveichik; 25th anniversary of his
death. Zhur.vys.nerv.delat. 6 no.3:494-497 My-Je '56.   (MLRA 9:11)

1. Kabinet istorii otechestvennoy fiziologii Instituta fiziologii
im. I.P.Pavlova Akademii nauk SSSR.
       (SOLOVEICHIK, DANIIL IL'ICH, 1885-1931)

ANDREYEVA, V.N.; FEDOROVA-GROT, A.K.

Pavel Pavlovich Pimenov, 1873-1956; obituary. ^{Z}hur.vys.nerv.dealt.
7 no.3:460-462 My-Je '57.   (MIRA 10:10)

1. Kabinet isotrii otechestvennoy fisologii Instituta fisiologii
im. I.P.Pavlova AN SSSR.
        (PIMENOV, PAVEL PAVLOVICH, 1873-1956)

ANDREYEVA, V.N., kand.biol.nauk

Survey of the development of Russian research on the physiology of
gastric digestion in the 19th century (till 1890). Trudy Inst. ist.
est. i tekh. 24:284-300 '58.   (MIRA 11:8)

    (STOMACH--SECRETIONS) (BIOLOGICAL RESEARCH)

ANDREYEVA, V.N.

Historical sketch on the development of Russian investigations on
the physiology of digestion in the oral cavity in the nineteenth
century (up to 1890). Trudy Inst. fiziol. 9:461-466 '60.
                                                    (MIRA 14:3)

1. Kabinet istorii otechestvennoy fiziologii (zaveduyuhchaya -
V.N.Andreyeva) Instituta fiziologii im. I.P.Pavlova.
                    (DIGESTION)

ANDREYEVA, V.N.

Interaction of conditioned food and devensive reflexes. Nauch.
soob. Inst. fiziol. AN SSSR no.1:13-15 '59.   (MIRA 14:10)

1. Laboratoriya fiziologii i patologii vysshey nervnoy deyatel'nosti
(zav. - F.P.Mayorov) Instituta fiziologii imeni Pavlova AN SSSR.
                    (CONDITIONED RESPONSE)

ANDREYEVA, V.N.

I.P.Pavlov in S.P.Botkin's therapeutic clinic at the Academy (1878-
1890). Fiziol. zhur 46 no.3:363-366 Mr '60.   (MIRA 14:7)

1. From the I.P.Pavlov Institute of Physiology, the U.S.S.R. Academy
of Sciences, Leningrad.
                (PAVLOV, IVAN.PETROVICH, 1849-1936)
                (BOTKIN, SERGEI PETROVICH, 1832-1889)

ANDREYEVA, V.N.

Ivan Petrovich Pavlov as dissertation examiner. Trudy Inst.
ist. est. i tekh. 41:294-323 '61.   (MIRA 15:2)

1. Kabinet istorii fiziologii Instituta fiziologii AN SSSR.
              (Pavlov, Ivan Petrovich, 1849-1936)

ANDREYEVA, V.N.

           ---'lem of correlation between the extinctive and supraliminal
inhibitions. Zhur. vys. nerv. deiat. 12 no.4:679-685 Jl-Ap '62.
                                                (MIRA 17:11)
1. Laboratory of Physiology and Pathology of Higher Nervous
Activity, Pavlov Institute of Physiology, U.S.S.R. Academy of
Sciences, Leningrad.

ANDREYEVA, V.N.

Interaction of supraliminal and external inhibition. Zhur.
vys. nerv. deiat. 14 no. 4:695-700 Jl-Ag '64. (MIRA 17:12)

1. Laboraotry of Physiology and Experimental Pathology of
Higher Nervous Activity, Pavlov Institute of Physiology,
U.S.S.R. Academy of Sciences, Leningrad.

DELIMARSKIY, Yu.K.; ANDREYEVA, V.N.; KAI : : : ., : . . .

Reaction of metal oxides with fused sodium metaphosphate. Izv,
AN SSSR. Neorg. mat. 1 no.1:150-155 Ja '65.   (MIRA 18:5)

1. Kiyevskiy tekhnologicheskiy institut pishchevoy promyshlennosti.

KRATIN, Yu.G.; ANDREYEVA, V.N.

Variations in the action of differentiation signals in conditioned
motor alimentary reflexes in cats. Zhur. vys. nerv. deiat. 16 no. 1:
3-13   Ja-F '66   (MIRA 19:2)

1. Laboratoriya fiziologii i patologii vysshey nervnoy deyatel'-
nosti Instituta fiziologii imeni I.P. Pavlova AN SSSR. Submitted
December 14, 1964.

L 44356-66   EWT(m)/EWP(k)/EWP(t)/ETI   IJP(c)   JH/JD/HW

ACC NR: AP6013482   SOURCE CODE: UR/0182/65/000/012/0020/0023

AUTHOR: Lisitsyn, V. D.; Andreyeva, V. N.; Tyanutov, A. G.

ORG: none

TITLE: Experimental study of the drawing of box shapes

SOURCE: Kuznechno-shtampovochnoye proizvodstvo, no. 12, 1965, 20-23

TOPIC TAGS: rimmed steel, brass, oscillograph, metal drawing, pressure measurement, metal press / 10kp rimmed steel, L62 brass, AD aluminum, MPO-2 oscillograph

ABSTRACT: The article presents the results of an experimental investigation of the drawing of box shapes of various materials: 10kp rimmed steel, L62 brass and AD aluminum, performed with the object of determining the drawing pressure and blankholder pressure as a function of punch stroke and time. The experiments were carried out in an industrial 65-ton drawing press on recording the stresses and pressures with the aid of wire strain gauges and an MPO-2 oscillograph. Analysis of the obtained oscillograms made it possible to determine the maximum drawing pressures for various drawing coefficients m_ϵ as well as the blankholder and edge-trimming pressures. As exemplified by the drawing of brass boxes (Fig. 1), during

UDC: 621.983.3

Card   1/4

L 44356-66

ACC NR: AP6013482

Fig. 1. Experimental curves of drawing pressure P_{dr} during the drawing of brass
boxes

the initial part of the forming process the curves of drawing pressure rise steeply; this cor-
responds to the period of travel of the punch from its initial position to a position at which the
centers of curvature of the punch and die coincide in the horizontal. The variation in kinematic
and dynamic parameters in the course of the drawing of box shapes was analyzed by plotting
combined curves of drawing pressure, blankholder pressure, punch travel and punch stroke
(Fig. 2). Initially, as the draw punch encounters the blank, the continuity of motion of the press
slider gets disturbed and its velocity sharply decreases. At the moment of impact of the punch

Card   2/4

L 44356-66
ACC NR: AP6013482

Fig. 2. Combined curves of variation in kinematic and dynamic parameters during the drawing of box shapes:
1 - punch travel; 2 - punch velocity; 3 - blankholder travel; 4 - drawing pressure; 5 - blankholder pressure

Card 3/4

SOV/68-58-10-13/25

AUTHORS: Yastrzhem'skaya, O.V., Andreyeva, V.S., Nenich, V.N.,
           Royter, M.K., Drinfel'd, P.Ye., and Bilym, L.M.

TITLE: From Experience of Putting the Indene-coumarone Resin
           Plant on the Kadiyevka Coking Works into Operation (Opyt
           puska i raboty tsekha inden-kumaronovykh smol na Kadiye-
           vskom koksokhimicheskom zavode)

PERIODICAL: Koks i Khimiya, 1958, Nr 10, pp 40 - 44 (USSR)

ABSTRACT: The plant was put into operation in 1955. The scheme of
           the operation of the plant as designed is shown in
           Figure 1 and changes introduced are shown in Figures 2
           and 3. Aluminium chloride is used as a catalyst in a
           proportion of 0.35% of the raw material. The polymeris-
           ation process begins at 20 - 30 $^{\circ}$C and is finished at
           110 $^{\circ}$C. The main difficulties were encountered in the
           distillation plant due to the incorrect design of the
           evaporators and due to an excessive corrosion of the
           condenser. All resin pipe-lines were found to be too long
           and complicated. Cooling drums for resin were
           insufficient. The initial losses of hydrocarbons amounted
           to 18-20% and were reduced (by unspecified methods) to

Card 1/2

SOV/68-58-10-13/25

From Experience of Putting the Indene-coumarone Resin Plant on the
Kadiyevka Coking Works into Operation

6-8%. Softening temperature of the resin produced
100 - 110 °C. It is pointed out that in order to decrease
corrosion, an enamelled distillation apparatus and a
reactor for the preparation of aluminium chloride complex
should be introduced. There are 3 figures.

ASSOCIATIONS: UKhIN and Kadiyevskiy koksokhimicheskiy zavod
(Kadiyevka Coking Works)

Card 2/2

S/068/62/000/003/002/003
E071/E435

AUTHORS: Nosalevich, I.M., Yeru, I.I., Yastrzhembskaya, O.V.
             Andreyeva, V.S.

TITLE: The production of lightly coloured and light resistant
             indine-coumarone resins by the method of catalytic
             hydrogenation

PERIODICAL: Koks i khimiya, no.3, 1962, 44-46

TEXT: The work was carried out in order to determine the
possibility of production of light coloured, stable and light-
resistant indine-coumarone resins, similar to good quality resins
produced in other countries.   The following types of catalyst
were tested: an industrial tungsten nickel sulphide on alumina
(tablets), molybdenum trisulphide (powder) and nickel-chromium
oxide (tablets).   The hydrogenation was done in two types of
autoclaves: a) with a stirrer, 350 rpm, b) by rotating about the
horizontal axis at 75 rpm.   As a starting material an industrial
product of catalysis containing 44 to 48% resin and about 0.25%
sulphur was used.   Catalysts were added in the form of a fine
powder in an amount of 10 wt %.   The hydrogenation product was

Card 1/3

The production of lightly coloured ...   S/068/62/000/003/002/003
E071/E435

filtered and steam distilled. The colour of industrial resins is usually determined by the iodine scale but the colour of the hydrogenated product was so much improved that the iodine scale could not be used and instead the chromate scale was applied. In addition, the iodine numbers of the starting (54 to 56) and the finished product (25 to 30) were determined. The resistance to light was determined by irradiation for 6 hours with ultraviolet light. It was found that with the sulphide catalyst at 200 to 250°C, the initial hydrogen pressure could be reduced to 30 to 40 atm without noticeable effect on the colour of the finished product. The colour of the starting product 35 units of the iodine scale, finished product - 0.5 units of the chromate scale. A decrease of the duration of heating from 60 to 30 min also had no influence on the quality of the product further decrease to 10 minutes brings about a noticeable deterioration. Replacement of hydrogen by coke-oven gas brings about some increase in the coloration of the resins. Experiments carried out in a rotating autoclave gave somewhat better results for both hydrogen and coke-oven gas, this is explained by the effect of hydrogenation in a
Card 2/3

S/068/62/000/005/001/002
E071/E435

AUTHORS: Yastrzhembskaya, O.V., Andreyeva, V.S.

TITLE: Application of boron fluoride in the production of
             indine-coumarone resins

PERIODICAL: Koks i khimiya, no.5, 1962, 44-46

TEXT: The results are described of experimental polymerization
of indine-coumarone fraction (heavy benzoles) in the presence of
phenol, acetic, alcohol and ether complexes of boron trifluoride
carried out in UKhIN.   It was found that the application of
phenol ($BF_3 \cdot 2C_6H_5OH$) and acetic ($BF_3 \cdot 2CH_3COOH$) complexes produces
resin with a coloration below 7 units of the iodine scale.   An
increase of the polymerization temperature up to $100-120\,^{\circ}C$ has no
influence on the colour of resins.   The best results were obtained
on polymerization in the presence of 0.5% (on the starting indine
coumarone fraction) of the phenol complex and temperature of 35 to
$100\,^{\circ}C$.   In this case the maximum yield of 52.4% was obtained,
while the corresponding yield with the acetic complex was 44.7%
(under standard experimental conditions).   In view of the high
Card 1/2

S/081/62/000/023/091/120
B101/B186

AUTHORS: Nosalevich, I. M., Yastrzhembskaya, O. V., Andreyeva, V. S.,
              Shapoval, L. D.

TITLE: Development of coumarone-indene resins production in the
              Ukraine

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 23, 1962, 678, abstract
              23P95 (Sb. nauchn. tr. Ukr. n.-i. uglekhim. in-t., no. 13 (35),
              1962, 136 - 143)

TEXT:: The method of producing coumarone-indene resins (CIR) was improved
so as to obtain neutral, bright, and light-resistant materials with a
low-ash content. Continuous operation was introduced. The finished
complex is separated in a settler-type supercentrifuge. The polymerizate
is stabilized by hydrogenation. New types of catalysts (BF_3 complexes)
are used. A description of the techniques, a flow sheet of the apparatus
for continuous CIR production, and flow sheets showing the hydrogenation of
the polymerizate and the separation of resins are given. [Abstracter's
note: Complete translation.]
Card 1/1

ANVAYER, S. I;ANDREYEVA, V. S;ZAK, N. N;MOROZOV, V. M.

Treatment of chronic alcoholism with thiurm. Zh. nevropat. psikhiat., Moskva 52 no.4:58-61 Apr 1952.   (CLML 22:2)

1. Of the Central Institute of Psychiatry of the Ministry of Public Health RSFSR (Director -- Docent D. Ye. Melekhov) and of the Clinical Psychiatric Hospital imeni Gannushkin (Head Physician -- V. N. Rybalko).

ANDREYEVA, V.S.

Effect of sodium fluoride on the calcium and organic and inorganic
phosphorus content of blood serum in puppies [with summary in English].
Fiziol.zhur. 43 no.12:1183-1186 D '57.   (MIRA 11:3)

1. Kafedra gospital'noy pediatrii Meditsinskogo instituta, Sverdlovsk.
        (FLUORIDES, effects,
            sodium, on blood calcium & phosphorus in young dogs (Rus))
        (CALCIUM, in blood,
            eff. of sodium fluoride in young dogs (Rus))
        (PHOSPHORUS, in blood,
            same)

ANDREYEVA, V. S., Candidate Med Sci (diss) -- "Some clinical and biochemical
data on preschool children suffering from dental fluorosis in the fluorosis-
endemic areas of the Urals". Sverdlovsk, 1958. 18 pp (Sverdlovsk State Med
Inst), 200 copies (KL, No 25, 1959, 139)

ANDREYEVA, V.S.

Effect of an excess of fluorine on the growing body. Fel'd. i akauh. 23 no.7:3-5 Jl '58   (MIRA 11:8)
(FLUORINE—PHYSIOLOGICAL EFFECT)

ANDREYEVA, V.S.

Some biochemical changes in children's blood during dental fluorosis.
Vop.okh.mat.i det. 4 no.6:25-29 N-D '59.   (MIRA 13:4)

1. Iz kafedry gospital'noy pediatrii (zaveduyushchiy - doktor med.,
nauk D.Ye. Sheynberg) Sverdlovskogo meditsinskogo instituta (direk-
tor - prof. A.F. Zverev).
   (FLUORINE--TOXICOLOGY)   (BLOOD)

ANDREYEVA, V.S.; GAVRILOVA, L.V.; LEVIN, V.M.; RESHETNIKOVA, Zh.V.

Acute psychotic states during antabuse treatment of chronic alcoholism.
Zhur.nev. i psikh.   59 no.6:674-678 '59.   (MIRA 13:1)

1. Bol'nitsa imeni Ganmushkina (glavnyy vrach V.N. Rybalka) i kafedra
psikhiatrii (zav. - prof. A.V. Snezhnevskiy) TSentral'nogo instituta
usovershenstvovaniya vrachey, Moskva.
                (DISULFIRAM, inj. eff.
                    psychoses (Rus))
                (PSYCHOSES, etiol. & pathogne.
                    disulfiram (Rus))

ANDREYEVA, V.S.

Investigation of the amount of calcium in the urine by Sul'kovich's
method for the early detection of intoxication during the treatment
of children with increased doses of vitamin D_2. Lab.delo 6 no.6:
54-56 N-D '60.   (MIRA 13:11)

1. Kafedra gospital'noy pediatrii (zav. - doktor meditsinskikh
nauk D.Ye.Sheynberg) Sverdlovskogo meditsinskogo instituta (dir. -
prof. A.F.Zverev)
          (CALCIUM IN THE BODY)
          (VITAMINS--D)

ANDREYEVA, V. S.,   CAND MED SCI,   "TREATING CHRONIC ALCO-

HOLISM WITH THIURAM (ANTABUSE)."   MOSCOW, 1961.   (SECOND

MOSCOW STATE MED INST IM N. I. PIROGOV).   (KL, 3-61, 229).

385

ANDREYEVA, V.S. (Moskva)

Characteristics of remissions in chronic alcoholism following
a course of antabuse treatment. Trudy Gos. nauch.-issl. inst.
psikh. 38:355-359 '63   (MIRA 16:11)

ANDREEVA, V.V.

PROCESSES AND PROPERTIES

The action of chemically active compounds on the mechanical properties of stainless steels. I. Ya. Klinov and V. V. Andreeva. *Vestnik Metalloprom*. 1937, No. 7, p. 56-62; *Khim. Referat. Zhur.* 1, No. 7, 106(1938).— The effects of hot and cold rolling on the chem. resistance of acid-resistant stainless steels were investigated, also the change of the mech. properties of these steels after the action of chemically active substances, and the crystal lattice structure of the steels. Samples from the "Serp i Molot" plant EYa1, EYa1 with Ti, EYa2, and Cr-Mn-Ni steel were used. The expts. were performed with Ca(HSO$_3$)$_2$ soln., and with a bisulfite base in an autoclave for 10 hrs. The rolling caused no changes either in chem. or in mech. properties. The loss of wt. was insignificant. The cold rolling increased the temporary resistance to rupture and lowered the viscosity of all investigated steels. For the steel EYa1 (hot rolling) and for EYa with Ti both media increased slightly the mech. properties. SO$_2$ in most cases lowered the mech. properties of steel.
W. R. Henn

METALLURGICAL LITERATURE CLASSIFICATION

S/080/62/035/006/002/013
D204/D307

AUTHORS: Andreyeva, V. V. and Alkeseyeva, Ye. L.

TITLE: The oxidation of titanium, zirconium, molybdenum and certain alloys.

PERIODICAL: Zhurnal prikladnoy khimii, v. 35, no. 6, 1962, 1175-1183

TEXT: The rates of oxidation of massive Ti, Mo, Zr, 90Ti10Mo and 92Ti5Cr3Al were studied in oxygen and in air, between 20 and 400°C. Progress of oxidation was assessed by the thickness of oxide scale formed, as measured by an optical polarization method. At room temperature, in air, Ti oxidized logarithmically, the scale reaching a thickness of 80 - 90 A.V. after 545 days. Between 50 and 250°C Ti oxidized faster in dry than in humid air. The oxidation of Zr was already appreciable at 50°C, of Ti and 90Ti10Mo alloy at 100°C and of Mo and 92Ti5Cr3Al at 150°C. At 150°C the scales on Ti, Mo and Zr reached 30 - 50 A.V. after 6 hours and were 250 - 400 A.V. thick after 6 hours at 250 - 350°C. Zirconium

Card 1/2

S/080/62/035/006/002/013
D204/D307

The oxidation of titanium ...

oxidized more rapidly than Mo at $250^{\circ}C$ or than Ti at $350^{\circ}C$. This was associated with the growth of monoclinic ZrO_2. Mo oxidized rapidly above $300^{\circ}C$ but an admixture of 10% Mo and Ti made this alloy better than Ti alone at the same temperature. The TiCrAl al- loy was particularly resistant to oxidation. In general the me- tals oxidized logarithmically at lower and parabolically at higher temperatures. The rate of oxidation is thought to be governed initially by the rate of formation of a thin scale as the tempe- rature is increased. The scales were found to be rutile for Ti, cubic ZrO_2 up to $250^{\circ}C$ and monoclinic ZrO_2 above $250^{\circ}C$ for Zr, MoO_3 up to $300^{\circ}C$ and $MoO_3 + MoO_2$ above $300^{\circ}C$ for Mo, solid solu- tion of TiO_2 and MoO_3 for 90Ti10Mo and (probably) a solid solution of Ti, Cr, Al oxides for the ternary alloy. Energies of activation for the oxidation processes ranged from 10 to 21.2 kcal/mole be- tween 200 and $350^{\circ}C$. The results are discussed. There are 8 figu- res and 2 tables.

– SUBMITTED: May 12, 1961

Card 2/2

35694

S/080/62/035/003/011/024
D217/D302

/P. /272

AUTHORS: Glukhova, A. I. and Andreyeva, V. V.

TITLE: Influence of additions of oxidizing agents to hydro-
              chloric acid solutions on the corrosion and electro-
              chemical behavior of zirconium and on alloys of the
              system zirconium-titanium

PERIODICAL: Zhurnal prikladnoy khimii, v. 35, no. 3, 1962, 567-572

TEXT: Alloys of the system Zr-Ti were prepared from the metal
iodides; the hafnium content of zirconium did not exceed 0.04%. The
alloys were cast into a water-cooled copper crucible in an elec-
tric arc furnace, with a tungsten electrode, and were then forged
at 800°C. The alloys were prepared and their mechanical properties
tested in the laboratory under the supervision of A. A. Kiselev.
The investigation of the influence of additions of oxidizing agents
to HCl solutions on the corrosion and electrochemical behavior of
Zr has shown that the potential at which passivation is destroyed
depends on the ratio between chlorine-ion content and ions of the

Card 1/3

Influence of additions ...   S/080/62/035/003/011/024
                               D217/D302

ASSOCIATION: Institut fizicheskoy khimii AN SSSR (Institute of
               Physical Chemistry AS USSR)

SUBMITTED: March 20, 1961

Card 3/3

35693

S/080/62/035/003/010/024
D217/D302

/8. /272

AUTHORS: Andreyeva, V. V. and Glukhova, A. I.

TITLE: Corrosion and electrochemical behavior of alloys of
              the system zirconium-titanium in hydrochloric acid
              solutions

PERIODICAL: Zhurnal prikladnoy khimii, v. 35, n. 3, 1962, 562-567

TEXT: The purpose of this investigation, in which the corrosion
resistance and the electrochemical properties of binary alloys of
the system Zr-Ti, as well as unalloyed Zr and Ti were studied in
HCl solution, was to establish general relationships between the
behavior of these metals and alloys and a number of factors (alloy
composition, concentration and temperature of solution and electro-
chemical polarization) and to develop new corrosion-resistant al-
loys. Various concentrations of HCl solution at 20, 40 and 100°C
were used in this study. It was found that whereas zirconium re-
mains practically unattacked by HCl up to 100°C at all concentra-
tions, the rate of corrosion of Ti increases considerably with in-

Card 1/3

Corrosion and electrochemical ...

S/080/62/035/003/010/024
D217/D302

crease in acid concentration and temperature. Polarization curves, obtained by the potentiostatic method, show that the cathodic regions of titanium readily dissolve in 20% HCl solution at 100°C. Passivation commences at a potential of -0.3 V (on the hydrogen scale). The anodic regions of Ti are passive. For Zr, a passive portion is observed in the anodic region at 40°C. However, at a potential of +0.3 V, the current density increases abruptly and pitting corrosion commences. On increasing the temperature to 100°C, the passive range in the anodic region decreases and at a potential of +0.2 V, the metal becomes active; the corrosion current increases and Zr is completely destroyed. The shape of the polarization curves changes with the nature of the metal and composition of the alloy. The results obtained support the assumption that the composition of the protective surface films of Zr-Ti alloys is a solid solution of mixed oxides, consisting of ZrO_2 and TiO_2. It is concluded that alloying Ti with Zr increases its corrosion resistance in HCl solutions. The higher the Zr content, the higher the stability of the alloy. There are 5 figures, 2 tables and 8 references: 5 Soviet-bloc and 3 non-Soviet-bloc. The references to the English-language

Card 2/3

$$S/598/6/000/006/030/034$$
$$D217/D303$$

18.6300

AUTHORS: Andreyeva, V.V., and Kazarin, V.I.

TITLE: Corrosion resistance and electrochemical properties
            of titanium and its alloys

SOURCE: Akademiya nauk SSSR. Institut metallurgii. Titan i
            yego splavy, no. 6, 1961. Metallotermiya i elektro-
            khimiya titana, 230 - 236

TEXT: 98.7 % pure Ti and binary Ti alloys with additions of Mo
and Zr were studied in solutions of various acids. Apart from the
corrosion method, the electrochemical potentiostatic method of
plotting polarization curves was used. The latter method enabled
the corrosion behavior of metal to be studied at a desired poten-
tial, maintained at a constant value by means of an electronic po-
tentiostat. The following relationships were studied for Ti: C.D.
against potential and corrosion against potential in 40 % H2SO4,
40 % H2SO4 + 5 % HNO3, and 40 % H2SO4 + 5 % HNO3 + 0.1 % NaF. The
influence of Zr and Mo content on the rate of corrosion of Ti in

Card 1/2

31040

S/598/61/000/006/030/034

· Corrosion resistance and electrochemical..D217/D303

H_2SO_4 solutions of various concentrations at various temperatures was investigated. Curves of C.D. against potential and corrosion against potential were plotted for Ti-Mo alloys in H_2SO_4 at 100°. The dependence of the critical anode current density on temperature and composition of Ti-Zr alloys in 40 % H_2SO_4 was investigated. The range of potentials within which Ti is passive, i.e. remains practically uncorroded in most agressive acid solutions, except solutions containing F ions, was defined. Titanium when alloyed with Zr and Mo results in materials of high mechanical properties and corrosion resistance. There are 6 figures and 6 references: 3 Soviet-bloc and 3 non-Soviet-bloc. The references to the English-language publications read as follows: N.P. Inglis and J.B. Cotton, Corrosion, Prevention and Control, 1958, 5, no. 11, 49; M. Stern, J. of the Electrochemical Soc., 1958, 105, 11, 638 - 647.

Card 2/2

S/762/61/000/000/007/029

AUTHORS: Andreyeva, V.V., Kazarin, V.I.

TITLE: Corrosion resistance of titanium and its alloys.

SOURCE: Titan v promyshlennosti; sbornik statey. Ed. by S.G.Glazunov.
          Moscow, 1961, 90-97.

TEXT: The paper comprises a state-of-the-art survey based on published
literature. Ti and its alloys may serve usefully in chemical-equipment construct-
ion. In some aggressive media the stability of Ti compares with that of Pt. Ti
excels over stainless steel by greater resistance against pitting, corrosion crack-
ing, and fatigue corrosion (in chloride solutions etc.). In large structures it may be
applied as a 1-2-mm thick cladding material. The corrosion resistance of Ti is
attributed to the formation of a protective surface film, the composition of which
depends on the conditions of its formation and exposure (cf. the authors, in Akad.
nauk SSSR, Dokl., no.4, 1957, 56-159; v.121, no.5, 1958, 873-876; v.123, no.6,
1958, 1048-1051). The film consists prevalently of TiO_2; at times, in HCl, it may
consist of TiH_2; within a certain concentration range in H_2SO_4, it may be formed of
variously constituted insoluble compounds of TiO_2, H_2SO_4, and H_2O. In solutions
containing F ions, H_2SO_4, and HCl (except for highly diluted low-temperature
solutions), oxalic acid, etc., Ti is unstable. Passivity may then be attained by anod-
ization (Tomashov, N.D., et al., Protection of Ti in H_2SO_4 and HCl by anodization.
Fil. VINITI, 1959, tema (paper) no.13, no. M-59-239/26) and by adsorption,
Card 1/2

Corrosion resistance of titanium and its alloys.   S/762/61/000/000/007/029

followed by partial chemosorption, of cations such as Cu^{2+} et al. (cf. Stern, M., J. Electrochem. Soc., v. 105, no. 11, 1958, 638-647; Roger, W., Leidheiser, H., Z. f. Elektrochemie, v. 62, no. 6/7, 1958, 619-830). The authors have shown that the protective effect is due to the presence of a certain quantity of Ti^{4+} ions in the H_2SO_4 and HCl which established an equilibrium with the TiO_2 of the surface film. The authors have shown, by the potentiostatic method and otherwise, that the presence of oxidizers, such as HNO_3, H_2O_2, O_2 (aeration), $KMnO_4$, et al., produces an oxidizing-reducing potential at which the Ti is passive (potentiostatic curves are depicted and interpreted in detail). Lastly, corrosion resistance through the formation of surface films may be achieved by suitable alloying (composition and characteristics are tabulated and graphed). Most effective additions: Mo, Zr, Nb. The significant favorable effect of a small (1.4%) addition of Al to a Ti+3%Mo alloys is noted. Basically, the alloying addition must be a metal which per se is more corrosion-resistant in the given aggressive medium than Ti alone. It must be capable of forming a protective surface film by solid-solution formation between the oxides of Ti and of the alloying addition. A most effective corrosion-protective improvement on Ti alloys is achieved by heat treatments which produce single-phase alloys with a wholly recrystallized structure. There are 5 figures, 6 tables, and 6 references (4 Russian-language Soviet, 1 German, 1 English-language).

ASSOCIATION: None given.

Card 2/2 .

BR

PHASE I BOOK EXPLOITATION   SOV/5956

Andreyeva, V. V., and V. I. Kazarin.

Novyye konstruktsionnyye khimicheski stoykiye metallicheskiye
   materialy (New, Chemically Stable Structural Metal Materials)
   Moscow, Goskhimizdat, 1961. 189 p. (Korroziya v khimicheskikh
   proizvodstvakh i sposoby zashchity, vyp. 17) 6000 copies printed.

Ed. (Title page): I. Ya. Klinov; Editorial Board of Series: N. A.
   Baklanov, I. Ya. Klinov, A. L. Labutin, G. V. Sagalayev (Chairman),
   P. D. Trebukov (Secretary), and P. G. Udyma; Ed.: S. M. Belen'kaya;
   Tech. Ed.: V. V. Kogan.

PURPOSE: This book is intended for technical personnel of chemical
   plants.

COVERAGE: The book reviews the properties and methods of producing the
   new, chemically stable structural materials (titanium-base alloys
   and zirconium-base alloys) currently being used. Materials which
   may see wide use in the future due to their valuable properties

Card 1/8

Card 2/8

5(4)
AUTHORS: Andreyeva, V. V., Kazarin, V. I.   SOV/20-123-6-25/50

TITLE: The Influence of the Ions of Quadrivalent ' Titanium Upon the
                Electrochemical Properties and the Corrosion Behavior of
                Titanium (Vliyaniye ionov chetyrekhvalentnogo titana na
                elektrokhimicheskiye svoystva i korrozionnoye povedeniye titana)

PERIODICAL: Doklady Akademii nauk SSSR, 1958, Vol 123, Nr 6, pp 1048-1051
                (USSR)

ABSTRACT: The present paper deals with the problem as to wether an
                increase of the superficial film in thickness increases the
                corrosion stability of titanium or not. The thickness of the
                film formed on the titanium surface during polishing cannot be
                measured optically since the initial values of the optical
                constants of a surface of pure titanium are not known. In the
                present case, only the increase in thickness of the already
                present film could be investigated. Within 180 days, the
                thickness of the film increased only by 17 - 22 Å . This
                increase is not mainly due to an increase of the film in
                thickness, but, apparently, to the diminishing of the defects
                in the lattice of titanium oxide. It is possible that there is
Card 1/4   an equilibrium state in which practically no corrosion of

The Influence of the Ions of Quadrivalent Titanium   SOV/20-123-5-25/50
Upon the Electrochemical Properties and the Corrosion Behavior of Titanium

titanium is observed. The equilibrium condition has the form

$$TiO_2 + 2H_2SO_4 \rightleftarrows Ti(SO_4)_2 + 2H_2O \quad \text{or} \quad TiO_2 + 4H^+ \rightleftarrows Ti^{4+} + 2H_2O ,$$

that is $[Ti^{4+}] / [H^+]^4 = K$. The investigations were carried
out in solutions of hydrochloric acid and of sulphuric acid.
According to the results obtained, the amount of Ti^{4+} necessary
for the maintaining of titanium in the passive state, depends on
the acid concentration and on the temperature of the solution.
A diagram shows the dependence of the corrosion rate of titanium
on the concentration of Ti^{4+} in 20% and in 36% solutions of
hydrochloric acid and in 40% solution of sulphuric acid. The
second diagram shows the dependence of the rate of corrosion of
titanium in a 40% solution of H_2SO_4 on the concentration of
Ti^{4+} and on the temperature of the solutions. In a 40% solution
of sulphuric acid at 20° and at 60°, 0.015 mol/l Ti^{4+} are
sufficient for keeping titanium in the passive state. If the
temperature of the solution increases to 100°, already

Card 2/4   0.1 mol/l of Ti^{4+} would be necessary. In solutions of

The Influence of the Ions of **Quadrivalent** Titanium   SOV/20-123-6-25/50
Upon the Electrochemical Properties and the Corrosion Behavior of Titanium

hydrochloric acid, a still higher concentration of Ti^{4+} would be necessary because of the higher solubility of TiO_2 .

Measurement of electrode potential time dependence while the titanium sample is submerged in a 40% sulphuric acid solution shows progressive titanium activation. In such a solution at room temperature, the dissolution of titanium begins approximately after 2 hours. According to the polarization curves of titanium in a 40% solution of sulphuric acid in the presence of 0.14 mol/l Ti^{4+} at 40° and 60°, hydrogen is generated after activation. Titanium is initially dissolved as a bivalent ion. If the solution contains an oxidizer (for example, dissolved oxygen) the reaction $Ti^{2+} - e \rightarrow Ti^{3+} - e \rightarrow Ti^{4+}$ occurs. The

Card 3/4

The Influence of the Ions of Quadrivalent Titanium   SOV/20-123-6-25/50
Upon the Electrochemical Properties and the Corrosion Behavior of Titanium

oxidation of titanium to Ti^{4+} is by far slower than that to Ti^{3+}. There are 4 figures and 8 references, 3 of which are Soviet.

ASSOCIATION: Institut fizicheskoy khimii Akademii nauk SSSR
(Institute of Physical Chemistry of the Academy of Sciences, USSR)

PRESENTED: July 25, 1958, by A. N. Frumkin, Academician

SUBMITTED: July 21, 1958

Card 4/4

5(4)

AUTHORS: .   Andreyeva, V. V., Kazarin, V. I.   SOV/20-121-5-30/50

TITLE: The Electrochemical Properties and the Corrosion Behavior
                of Titanium in Solutions of Sulfuric Acid (Elektro-
                khimicheskiye svoystva i korrozionnoye povedeniye titana
                v rastvorakh sernoy kisloty)

PERIODICAL: Doklady Akademii nauk SSSR, 1958, Vol 121, Nr 5,
                pp 873 - 876 (USSR)

ABSTRACT: The velocity of dissolution of titanium in solutions
                of sulphuric acid depends in a very complicated manner
                on the concentration of this solution. There are 2
                maxima of the velocity of solution of titanium; one
                of them corresponds to a 40% concentration, the other -
                to a 75% concentration. The low velocity of the
                dissolution of titanium in diluted solutions of sulfuric
                acid (first minimum) implies a protecting influence of the
                natural oxide film developed on the titanium surface
                by the action of the air. In the region 50-70% of H_2SO_4

Card 1/3   concentration, the velocity of the corrosion of

The Electrochemical Properties and the Corrosion   SOV/20-121-5-30/50
Behavior of Titanium in Solutions of Sulfuric Acid

titanium does not vary if the temperature increases from $30°$ to $50°$, the losses of titanium are slightly higher. The investigation of the system $TiO_2.SO_3.H_2O$ proves the possibility of the formation of 2 compounds of TiO_2 with H_2SO_4, the solubility of which at $100°$ is extraordinarily low for concentrations of 50-70%. These compounds have the following composition) $TiOSO_4.H_2O$ and $Ti_2O(SO_4)_3.5H_2O$ with the ratios $TiO_2:SO_3:H_2O$ = 1:1:1 for the first compound and 2:3:5 for the second compound. This was also confirmed by an experiment in which the variation of the potential in a 60% solution of H_2SO_4 was measured as a time function. In those sulfuric acid solutions which correspond to the maxima and minima of the solution velocity of titanium, the electrode potentials have different values. This implies a dif-ferent character of the reactions on the surface electrode.

Card 2/3   The activation energy of the ionization of the metal

The Electrochemical Properties and the Corrosion   SOV/2o-121-5-3o/5o
Behavior of Titanium in Solutions of Sulfuric Acid

             has the value 16,7 kcal/mol. The polarization curves
of the anode and of the cathode have horizontal parts
which correspond to an intensive solution of the metal.
The generation of oxygen on the titanium surface begins
at a sufficiently high overvoltage, i.e. $\sim$ + 2V. Numerous
further experimental data are given in this paper. There
are 4 figures and 4 references, 3 of which are Soviet.

ASSOCIATION: Institut fizicheskoy khimii Akademii nauk SSSR (Institute
of Physical Chemistry, AS USSR)

PRESENTED: April 10, 1958, by A.N.Frumkin, Academician

SUBMITTED: April 10, 1958

Card 3/3

ANDREYEVA, V.V.

PROCESSES AND PROPERTIES INDEX

*On the Reaction of Sulphur Dioxide on Metals and Alloys of Soviet Manu-
facture. I. J. Klinov and V. V. Andreeva (*Khimicheskoe Mashinostroenie*
(*Chem. Machinebuilding*), 1966, (4), 31-34).—[In Russian.] The investigation
dealt mainly with steels and pig irons. Of the non-ferrous metals various
bronzes were tested—all of them proved unstable to sulphur dioxide. Lead
containing 8% antimony was particularly resistant.—N. A.

METALLURGICAL LITERATURE CLASSIFICATION

ANDREYEVA, V.V.

The Chemical Stability Towards Moist Sulphur Dioxide of Metals and Alloys of Soviet Manufacture. I. Ya. Klinov and V. V. Andreeva (Zhurnal Khimicheskoi Promishlennosti (J. Chem. Ind.), 1936, 13, 1474-1477; C. Abs., 1937, 31, 2142).—[In Russian.] Cf. Met. Abs., 1936, 3, 542. Chromium-nickel and chromium-nickel-manganese steels are resistant to the action of moist sulphur dioxide. Addition of titanium and molybdenum reduces the resistance. Other metals are unsuitable under these conditions.—S. G.

ANDREYEVA, V. V.

*Acid-Resistant Alloys for Sulphite Pulping. V. V. Andreeva and N. K. Grigorieva (*Bumashnaia Promish.* (*Paper Ind.*), 1938, 16, (10), 28-34; C. Abs., 1939, 33, 6653).—[In Russian.] (Y. *Met. Abs.*, 1937, 4, 245. The resistance to corrosion of some 60 specimens of cast irons, steels, and alloys of copper, lead, tin, aluminium, and antimony was tested in the laboratory under conditions simulating those of sulphite pulping and regeneration. The non-ferrous alloys proved to be unstable.—N. B. V.

A.I.A.-S.L.A. METALLURGICAL LITERATURE CLASSIFICATION

ANDREYEVA, V.V.

C4

Application of the reflectometric method to the investi-
gation of corrosion of metals. I. V. Krotov and V. V.
Andreeva. Trudy Soveshchaniya Voprosam Korrozii
1940, 319-30; Khim. Referat. Zhur. 1940, No. 7, 136.—
The reflectometric method is the most simple optical
method for investigating metal surfaces. It is less ac-
curate than the polarized-light method, but more simple in
its application and it permits to study the kinetics of the
corrosion processes. The method is based on the reduc-
tion of the intensity of light (detd. by photoelements)
reflected by the surface of the corroded elements. K
and A. constructed an app. with converging light rays
(0.5-1.0 mm. slit) which dets. not only the corrosion
processes as a whole, but gives also an insight on local
phenomena taking place. Armco steel (3 × 4 cm.)
polished with a paste contg. Cr₂O₃ and degreased with
benzene and alc. was investigated (1) in water vapors
with and without the access of air and in boiling water and
(2) in a boiling 0.1% NaOH soln. and over its vapors
(without the access of air). The duration of the expts.
was 2, 4, 10 and 30 hrs. Two photograms produced 3
lines of light beams reflected by the galvanometer mirror
from the surface of the metal, both polished and corroded.
O plays an important role in the corrosion process in water
vapors, leading usually to local corrosion which increases
with the concn. The total area of corrosion differs only
slightly from that obtained with a very small access of air,
but its local character is better expressed. Corrosion over
vapors of boiling NaOH solns. decreases, but local cor-
rosion remains. Corrosion is of a local character in boiling
water. The reflectometric method detns. quantitatively
the intensity of corrosion in water, in solns. and in vapors.
A more detailed investigation of local corrosion phenom-
ena is possible from decreasing the cross section of the beam
of light passing through the slit.   W. R. Henn

SOV/137-58-9-19451

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 9, p 187 (USSR)

AUTHOR: Andreyeva, V.V.

TITLE: Measurement of the Thickness of Thin Films on Metals by the
            Optical Polarization Method (Izmereniye tolshchin tonkikh
            plenok na metallakh opticheskim polyarizatsionnym metodom)

PERIODICAL: Tr. In-ta fiz. khimii AN SSSR, 1957, Nr 6, pp 79-98

ABSTRACT: The experiment of the application of the optical-polariza-
            tion Drude-Tronstad method for the study of the corrosion pro-
            cess and the passivation of metals is described. The method
            permits the measurement of very fine films (F), of the order
            of 2-300 angstrom, without disrupting their continuity and while
            conducting other, for example, electrochemical, measure-
            ments at the same time. It is shown that the oxide F forming
            on Fe in dry air at 25°C and atmospheric pressure when mea-
            sured directly following the introduction of air into a vacuum
            container, has a thickness of the order of 10-19 angstrom.
            After staying under the same conditions for 24 hours the thick-
            ness of F increases by 4-9 angstrom, but during the following
Card 1/2   30 days its thickness does not vary. The maximum thickness

SOV/137-58-9-19451

Measurement of the Thickness of Thin Films on Metals (cont.)

of the F formed amounts to 16-23 angstrom. The thickness of F on speci-
mens kept in a desiccator for three years remained within the limit of the
same 16-23 angstrom. The growth of surface F on Ti and Al at 25° and 40%
relative humidity practically ceases after 70-75 days reaching an ultimate
thickness of 45-55 angstrom on Ti and 30-50 angstrom on Al. The oxide F
on Cu after 140 days attains a thickness of 150 angstrom, and after being
kept for three years in a desiccator it becomes visible in contrast to the invis-
ible F on Ti and Al kept under the same conditions. The thickness of F on
Ti and Al is the sum of the thicknesses of the F proper and of the polymo-
lecular layer of adsorbed gas or of the mixture of gas and water (depending
on the composition of the medium), while on the surface of Ag and Pt at
room temperature F form not as the result of the chemical oxidation pro-
cess, but owing to the physical adsorption of gases. Bibliography: 19
references.

P.S.

1. Thin films--Measurement   2. Iron oxides   3. Thin films--Testing equipment
4. Thin films--Test results

Card 2/2

ANDREYEVA, V. V.   and KASANYIN, V. Y.

"Elektrochemische und Korrosionserscheinungen von Titan und Titanlegierungen."

paper submitted for the Congress on Corrosion, Budapest, 24-30 Sept 1958.

Inst. of Physical Chem., Acad. Sci. USSR.

AUTHORS: Andreyeva, V. V., Shishakov, N. A.   SOV/76-32-7-35/45

TITLE: On the Thickness of Oxide Films on Some Metals as Shown by Data
                From Electron Diffraction and Optical Investigations (O tolshchi-
                ne okisnykh plenok na nekotorykh metallakh po dannym elektrono-
                graficheskikh i opticheskikh issledovaniy)

PERIODICAL: Zhurnal fizicheskoy khimii, 1958, Vol 32, Nr 7,
                pp. 1671 - 1672 (USSR)

ABSTRACT: Based on the comparative investigations mentioned above it is
                assumed that a reversible polymolecular adsorption takes place
                at metal surfaces besides the monomolecular adsorption. In the
                electron diffraction determinations in vacuum a thickness of
                the layer of from 10 to 20 $\text{\AA}$ is found, while the optical
                measurements yield an almost twice as great value. In the first
                case, therefore, a partial evaporation of the film may have
                taken place, which in the second case is regarded as oxide film.
                In order to verify this assumption pertinent experiments were
                carried out and it was found that in aluminium electron
                diffraction measurements show a layer of aluminium and oxygen ions
Card 1/3   which is not thicker than 10 $\text{\AA}$, while optical data in the case

On the Thickness of Oxide Films on Some Metals as   SOV/76-32-7-35/45
Shown by Data From Electron Diffraction and Optical Investigations

of an air contact of the aluminium surface show a thickness of 21 - 22 Å. In the first case it would thus be the oxide film which is dealt with, while in the second case the oxide film and the polymolecular layer are present, which probably consists of oxygen and water traces. In the case of a pressure drop to 10^{-7} torr the film thickness decreases to 9 Å . When atmospheric pressure is restored it increases reversibly. Similar observations were made with iron and titanium, while experiments with platinum and gold showed that at normal temperature only the adsorption layer is present which completely disappears in vacuum, so that no film layer may be found by electron diffraction methods. At raised temperatures oxide films were also found in vacuum and it is assumed that this is an adsorption layer of molecular oxygen. There are 1 table and 3 references, 3 of which are Soviet.

ASSOCIATION: Akademiya nauk SSSR, Institut fizicheskoy khimii, Moskva (Moscow, Institute of Physical Chemistry, AS USSR)

Card 2/3

On the Thickness of Oxide Films on Some Metals as   SOV/76-32-7-35/45
· Shown by Data From Electron Diffraction and Optical Investigations

SUBMITTED: April 2, 1957

                1. Oxide films--Physical properties   2. Oxide films--Measurement
                3. Oxide films--Electron diffraction analysis   4. Oxide films
                --Optical analysis   5. Metals--Adsorptive properties

Card 3/3

ANDREYEVA, V V

(7)   PHASE I BOOK EXPLOITATION   SOV/3399

Shishakov, Nikolay Alekseyevich, Valentina Vladimirovna Andreyeva, and
   Nina Konstantinovna Andrushchenko

Stroyeniye i mekhanizm obrazovaniya okisnykh plenok na metallakh (Structure
   and Mechanism of Formation of Oxide Films on Metals) Moscow, AN SSSR,
   1959. 194 p. Errata slip inserted. 2,500 copies printed.

Sponsoring Agency: Akademiya nauk SSSR. Institut fizicheskoy khimii

Resp. Ed.: V.I. Kasatochkin, Doctor of Chemical Sciences; Ed. of Publishing
   House: A,A. Babad-Zakhryapin; Tech. Ed.: V.V. Bruzgul'.

PURPOSE: The book is intended for students and workers in the field of metallog-
   raphy, particularly those interested in the study of the structure of the surface
   of metals and the mechanism of their interaction with oxygen.

COVERAGE: Having analyzed the various existing theories on the structure of oxide
   films on metals, the authors arrived at the conclusion that all existing theo-
   ries were inadequate and had to be supplemented with new experimental data.

Card 1/7

Structure and Mechanism of Formation (Cont.)   SOV/3399

The main purpose of the book is therefore the systematization of experimental data in this field. Basically, the work presents the investigation of the interaction of metals and pure oxygen or air. Considerable attention has been given to the investigation of the surface of the metal itself, since this knowledge is the prerequisite for a correct understanding of the mechanism of oxide film formation on metal surfaces. Included are 57 tables and 17 photographs. There are 132 references, of which 49 are Soviet.

TABLE OF CONTENTS:

Card 2/7

Structure and Mechanism of Formation (Cont.)   SOV/3399

Card 4/7

Structure and Mechanism of Formation   (Cont.)   SOV/3399

Card 6/7

ANDREYEVA, V. V.

Third prize (imeni D. K. Chernov) awarded to Engineer V. V. Andreyeva and Engineer V. I. Kazarin (Institute of Physical Chemistry, Ac. Sc., USSR), Engineer G. P. Danilova and Engineer Ye. A. Kamenskaya (Institute of Rare Metals) for their paper "Investigation of the Strength of Titanium Base, Corrosion Resistant Alloys".

Results of the 1958 Competition for Obtaining imeni D. K. Chernov and imeni N. A. Minkevich Prizes, Metallovedeniye i termicheskaya obrabotka metallov, 1959, No. 6, pp 62-64

5(4),18(7)
.AUTHORS: Andreyeva, V. V., Kazarin, V. I.   SOV/20-128-4-31/65

TITLE: The Influence of Alloy Elements on the Corrosion Resistance
                   and Electrochemical Behavior of Titanium

PERIODICAL: Doklady Akademii nauk SSSR, 1959, Vol 128, Nr 4,
                   pp 748-751   (USSR)

ABSTRACT: The corrosion resistance (CR) of titanium alloys was des-
                   cribed by the authors in earlier papers (Refs 1-9). The
                   influence of the following elements on the CR of titanium in
                   acids had been investigated: Cu, Zr, Nb, Mo, Ta, V, Al, Cr,
                   Fe, Ni, Mn, Si, and B. These elements can be divided into
                   3 groups: (1) Elements raising the CR of Ti (Mo, Ta, Al, Zr, V);
                   (2) elements causing no change in the CR (Si), and (3) elements
                   reducing the CR (Fe, Mn). Figure 1 shows that the elements
                   of the 1st group act already in additions between 1 and 2.5%.
                   A further increase in the addition raises the CR achieved only
                   slightly except for Zr which, in an addition of 50%, makes
                   the CR in H_2SO_4 and HCl equal to that of pure Zr. Figure 2
                   shows the curves of anodic and cathodic polarization of Ti and
                   its alloys with 10% Nb, Ta, Mo. For Ti + 10% Ta, the anodic

Card 1/2

The Influence of Alloy Elements on the Corrosion
Resistance and Electrochemical Behavior of Titanium   SOV/20-128-4-31/65

current density exhibits the lowest value. Figure 4 shows the
corrosion of alloys with 10% Mo, Nb, Ta. There is a linear
dependence between the logarithm of the corrosion rate and $\frac{1}{T}$.
On the basis of the semiconductor theory for corrosion-
protective films (Wagner, Refs 10-12, Hauffe, Refs 13-15),the
distribution of oxygen ions and electrons in the defective
spots of the lattice is discussed, and the following conclu-
sion is drawn: The addition of a metal with higher valency
than that of titanium reduces the defective spots available
for O-ions by the appearance of an additional number of free
electrons, thus raising the CR of Ti. The opposite phenomenon
occurs when a metal of lower valency than that of Ti is added.
There are 4 figures and 20 references, 10 of which are Soviet.

ASSOCIATION: Institut fizicheskoy khimii Akademii nauk SSSR (Institute of
                Physical Chemistry of the Academy of Sciences, USSR)

PRESENTED: April 28, 1959, by A. N. Frumkin, Academician

SUBMITTED: April 15, 1959

Card 2/2

PHASE I BOOK EXPLOITATION SOV/2762

Vsesoyuznoye soveshchaniye po splavam redkikh metallov.

Redkiye metally i splavy; trudy ... (Rare Metals and Alloys; Transactions of the First All-Union Conference on Rare-Metal Alloys) Moscow, Metallurgizdat, 1960. 348 p.; 3,150 copies printed.

Sponsoring Agencies: Redkollegiya sektsii SSSR. Institut metallurgii; USSR.

PURPOSE: This collection of articles is intended for metallurgical engineers, physicists, and workers in the machine-building and radio-engineering industries. It may also be used by students of schools of higher education.

COVERAGE: The collection contains technical papers which were presented and discussed at the First All-Union Conference on Rare-Metal Alloys, held in the Institute of Metallurgy, Academy of Sciences USSR in November 1957. Results of investigation of rare-metal alloys, titanium, and copper-base alloys with additions of rare metals are presented and discussed along with investigations of properties of rare metals. The effect of rare-earth metals on properties of magnesium alloys and steels is analyzed. The uses of rhenium as a degasifying catalyst, electroplating material, and material suitable for making plugs for automobile, electrical systems are discussed. Also, the effect of the addition of certain elements on the properties of heat-resistant steel is examined and alloys with special physical properties (particularly the magnetic alloys) are discussed. Personalities are mentioned. Soviet and non-Soviet references accompany some of the articles.

PART II. TITANIUM, AND COPPER-BASE ALLOYS WITH RARE-METAL ADDITIONS

Rare Metals (Cont.)

Andreyeva, A.I., A.I. Olshanov, L.L. Solovyev, and M.T. Kirillov. Corrosion Resistance of Zirconium and Its Alloys 156

PART IV. RARE-EARTH METALS AND THEIR EFFECT ON PROPERTIES OF MAGNESIUM ALLOYS

Drobotko, P.I., and I.S. Galpiverko. Rare-Earth Elements and Possibilities of Producing the 171

Ioffe, I.M., V.M. Royzin, and I.M. Yefimov. Production of Aluminum-Cerium, Titanium-Lanthanum, Magnesium-Cerium, Magnesium-Lanthanum, and Magnesium-Neodymium Addition Alloys by Electrolysis 180

Grohbova, V.P., and Ye.M. Savitskiy. Investigation of Physicochemical Interaction of Rare-Earth Metals with Magnesium, Iron, Chromium, and Titanium 189

Mikheyev, V.S., and M.Ye. Dorn. Hydrides of Rare-Earth Metals and Possibilities of Their Practical Utilization 202

Card 5/8

18. 1285

AUTHORS: Klinov, I.Ya,, Professor, Doctor of Technical Sciences; Andreyeva,
            V.V., Candidate of Chemical Sciences

TITLE: Titanium and Its Alloys as Construction Materials

PERIODICAL: Khimicheskoye Mashinostroyeniye, 1960, No. 4, pp. 5 - 8

TEXT: The article reviews the results of tests carried out by M.A. Vorob'-
yeva on the suitability of titanium and its alloys for construction purposes.
Their mechanical properties depend on the content of oxygen, nitrate and nitro-
gen which increase their hardness and fatigue strength while reducing their plas-
tic properties. The best plastic properties were observed in titanium obtained
by the iodine method. The fatigue stress of BT1 (VT1) titanium decreases from
60 to 23 kg/mm^2 at 400°C and the yield strength from 47 to 19 kg/mm^2 at 400°C.
Low temperatures increase the fatigue stress and reduce the plasticity of tita-
nium. Although the electrode potential of titanium is negative, its surface is
purified by oxygen which renders the potential positive. This is probably due
to the formation of a protective TiO_2 coating. During corrosion in hydrochloric
acid, titanium is sometimes covered by a protective TiH_2 coating. Sulfuric acid

Card 1/4

Titanium and Its Alloys as Construction Materials

S/184/60/000/004/002/021
A109, A029

produces insoluble compounds of TiO_2 with H_2SO_4, and nitric acid produces H_2TiO_3 coating. Both coatings protect the metal from acids. From the economic point of view the use of titanium is feasible when high corrosion resistance under continuous operating conditions is required and when no corrosive impurities are admitted. Pure titanium rather than its alloys should be used whenever it is considered sufficiently corrosion-resistant and when no additional alloying is required. Figure 2 shows results of corrosion tests carried out on four types of titanium in 50%-sulfuric acid at 50°C. The influence of admixtures on the corrosion rate of titanium in 63%-nitric acid at 50°C is shown in Figure 3. The corrosion rate can be reduced to zero by addition of HNO_3, $K_2Cr_2O_7$, $KMnO_4$, HNO_3 and H_2O_2 oxidizers or other compounds. These admixtures raise the titanium solution potential to a higher value than the Flade potential. Passivation can also be obtained by addition of Cu^{2+}, Fe^{3+}, Pt^{4+}, Pd^{4+}. Au^{3+}, etc. Titanium is suitable for construction of chemical machinery provided that the passivation has been achieved by formation of a protective coating and that the corrosion is not accelerated by changing operating conditions. Dry gaseous chlorine effects strong corrosion of titanium. In reaction with dry chlorine an inflammation of chloride may result. The presence of as little as 0.005% of moisture inhibits corrosion. At 100°C the corrosion rate of titanium in moist chlorine does not

Card 2/4

Titanium and Its Alloys as Construction Materials

S/184/60/000/004/002/021
A109/A029

exceed 0.0025 mm/year. Titanium retains its resistance in many organic solutions in which 18-8 nickel-chromium steels corrode. It is quickly corroding in boiling citric acid and in oxalic acid. Corrosion resistance and mechanical properties can be greatly improved by alloying with metals of higher corrosion resistance. The time effect on corrosion of cast titanium and titanium-based alloys in a 1 N sulfuric acid solution at 50°C was studied. The highest corrosion resistance was found in titanium-nickel alloys. Variation of corrosion rate depending on the content of molybdenum and the concentration and temperature of sulfuric acid was investigated. The highest corrosion resistance was achieved by addition of Mo, Ta, Nb, Zr and Cu. Titanium can be used either as basic material or for plating. In the latter case care should be taken that linear expansion coefficients do not differ too strongly from each other as this may lead to deformation or even destruction of the plating. In view of this, titanium can be recommended for plating of carbon and stainless steels. There are 9 figures, 1 table and 2 Soviet references.

Card 3/4

83559

also 2308

18.1285

S/020/60/134/001/011/021
B004/B060

AUTHORS: Andreyeva, V. V., Alekseyeva, Ye. A.

TITLE: Thin Oxide Films on Titanium, Zirconium, Molybdenum and
               Titanium Alloys

PERIODICAL: Doklady Akademii nauk SSSR, 1960, Vol. 134, No. 1,
               pp. 106 - 109

TEXT: The authors wanted to study the kinetics of the oxidation of Ti,
Zr, Mo, and the alloys Ti+10% Mo and Ti+3% Al+5% Cr in the temperature
range 50-400°C. The thickness of the thin, invisible oxide films was
measured by means of a previously described (Refs. 1,4,5) optical polari-
zation method which is based on the ellipticity of reflected light. The
oxidation took place in a tubular furnace in an oxygen stream. The thick-
ness of the oxide films was measured every 60 min. Figs. 1,2 show the
results of measurement; Table 1 lists the film thicknesses attained
after 6 h. Zirconium is noticeably oxidized already at 50°C, titanium
and the alloy Ti+10%Mo at 100°C, molybdenum and the alloy Ti+3%Al+5%Cr
at 150°C. The oxidation is fast at the beginning, and gradually stops

Card 1/3

83559

Thin Oxide Films on Titanium, Zirconium,   S/020/60/134/001/011/021
Molybdenum, and Titanium Alloys   B004/B060

as soon as the oxide film attains a certain thickness. The increase in
film thickness, L, can be represented by equation (1): $L = k \log(k_1 t + k_2)$.

At high temperatures, however, the relation (2) $L^2 = k_3 t$ (Fig. 3) holds.

For the metals and alloys examined, Table 1 supplies the temperature
ranges in which the logarithmic or the parabolic law holds. Up to 800°C,
the oxide film on titanium consists of TiO_2 (rutile). TiO layers are
formed above 800°C (immediately on the metal), Ti_2O_3 (middle layer) and

TiO_2 (external layer). On zirconium, ZrO_2 of a cubic structure forms up

to 250°C, and ZrO_2 of a monoclinic structure above 250°C. In the case of

molybdenum, the oxide layer consists of MoO_3 up to 300°C. Above 300°C,

MoO_2 is formed additionally due to dissociation. Fig. 3 further shows
oxidation curves for chromium and aluminum, which are taken from the
paper by T. N. Krylova (Ref. 9). These metals form only Cr_2O_3 and Al_2O_3,
respectively. The activation energy was calculated from the slope of
the linear function $\log k = f(1/T)$ (Table 1). The mechanism underlying

Card 2/3

83559

Thin Oxide Films on Titanium, Zirconium,   S/020/60/134/001/011/021
Molybdenum, and Titanium Alloys   B004/B060

the oxidation of zirconium and molybdenum differs from that of the
oxidation of titanium and the alloy Ti+10%Mo. A mixed oxide, $TiO_2 + xMoO_3$,
is formed in the latter case. The resistivity to heat is thus improved.
The high resistivity of the alloy Ti+3%Al+5%Cr to oxidation is explained
by the formation of a mixed oxide of the spinel type. Fig. 4 shows the
oxidation of titanium at 50-250°C in dry and moist, fully saturated air.
In dry air, the oxide layer becomes twice as thick as in moist air. In
the latter, however, the oxide layer is more compact and contains fewer
defects. At 250°C, the water binding is loosened, and the thickness of
the oxide layer attains the same value as in dry air. There are 4 fig-
ures, 1 table, and 12 references: 9 Soviet, 2 US, and 1 German.

ASSOCIATION: Institut fizicheskoy khimii Akademii nauk SSSR (Institute
              of Physical Chemistry of the Academy of Sciences USSR)

PRESENTED: April 28, 1960, by A. N. Frumkin, Academician

SUBMITTED: April 28, 1960

Card 3/3

S/133/61/000/002/009/014
A054/A033

AUTHORS: Pakhaluyev, K.M., Medvedeva, I.V., Andreyeva, V.V., and Kul'kova,
            M.N.

TITLE: Oxidation and Decarbonization of Steels in Heating Furnaces Fired
         With Natural Gas

PERIODICAL: Stal', 1961, No. 2, pp. 160-163

TEXT: At the zavod "Krasnyy oktyabr" ("Krasnyy octyabre" Plant) and the
VNIIMT it was found that the average metal losses due to cindering amount
to 2.16-2.77% of the charge weight for 6-ton ingots and to 1.36-1.88% for
blooms and slabs, when heating furnaces fired with masut or natural gas are
used. In order to study the processes of cindering and decarbonization and
to find ways to reduce these processes simultaneously, 7 steel grades were
investigated under complete and incomplete combustion of natural gas. The
tests were carried out on specimens (rolled bars) 50 mm in diameter and
200 mm long. The decarbonized surface layer of the samples was removed and

Card 1/11
      6

S/133/61/000/002/009/014
A054/A033

Oxidation and Decarbonization of Steels in Heating Furnaces Fired With
Natural Gas

the surface was polished. Delayed cooling of the specimens was effected by
fitting to one of the furnace openings a brick-lined chamber, into which
technically pure nitrogen was blown. The furnace was fired with Saushinsk
natural gas (CO_2: 0.25%; O_2: 0.20%; CH_4: 97.90%; C_mH_n: 0.17%; N_2: 1.48%).
When the degree of oxidation of the specimen was determined, they were held
in the furnace for a given time until a constant temperature was reached,
then they were quickly removed and cooled in water. When both oxidation and
decarbonization were investigated the specimen was put after heating in the
cooling chamber filled with nitrogen. Besides, the samples were pickled (in
20%-hydrochloric acid at 45-60°C) weighed and measured. The difference in
weight of the samples before and after heating gave the amount of cinder;
the depth of decarbonized layer was defined by microanalysis and the excess
air in a BTИ-(VTJ)-type gas-analyzer. Altogether 82 tests were carried out
with natural gas firing with excess air factors varying between 0.6 and 1.6.
The samples were heated to 700-1250°C, the holding time at constant tempera-

Card 2/11
      6

S/133/61/000/002/009/014
A054/A033

Oxidation and Decarbonization of Steels in Heating Furnaces Fired With
Natural Gas

ture was 1/2-3 hours. The relationship between the amount of oxidized metal
and the factor of excess air in the combustion products of natural gas is
plotted in figs.1-2, showing that metal cinder quickly decreases with a re-
duction of the excess air factor when heating to 1000^bC and more. If it is
technologically possible to lower somewhat the very high temperatures of the
metal during heat treatment, the metal losses due to cindering could be re-
duced considerably. Fig.4 shows that by cutting down the holding time as far
as permitted by the technology, cindering can also be decreased. When the
effect of air excess on decarbonization was studied, the decrease of the air
excess factor was found to be accompanied by a thinner decarbonized layer.
The lowering of the oxidizing effect of combustion products of natural gas
were moreover observed to affect the metal and the carbon content of the me-
tal simultaneously. It is, therefore, possible to reduce oxidation and de-
carbonization when heating under "non-oxidizing" conditions. From the test
results it was concluded that the total excess of oxidants - as compared with
the equivalent amount - quickly declines with a decreasing value of "a"; on
Card 3/14

S/133/61/000/002/009/014
A054/A033

Oxidation and Decarbonization of Steels in Heating Furnaces Fired With
Natural Gas

an average the combustion products of gas lose their oxidizing effect at me-
tal temperatures of 800, 1000, 1200°C (with an air excess factor of 0.54).
Based on these data it is possible to attain a "non-oxidizing" heating of
steel in natural-gas fired free flame furnaces. However, at very low "a"
values the incomplete combustion results in a temperature decrease of the
combustion products and additional heat with preheated fuel and air has to
be supplied. The conditions of non-oxidizing heating for various furnaces
(for instance for roller type furnaces for blooms) are determined by the fol-
lowing temperatures

	Bloom	Billet	Sheet
Temperature of the combustion product of the fuel, °C, ca	1400	1000	1050-1100
Calorimetric temperature of combustion, °C, ca	1870	1430	1500-1570
Temperature of air preheating, according to fig.9, °C	840	130-160	250-400

Card 4/14